

## AXIS P3367-V Network Camera

5-megapixel, light-sensitive with remote focus and zoom

AXIS P3367-V is a fixed dome network camera that offers superb video performance in HDTV 1080p/5 MP resolution. It complies with the SMPTE 274M standard and can cover a large area with exceptional detail and light sensitivity. Wide dynamic range and day/night functionality provides high image quality even in low-light conditions. With multi-view streaming, the full view and up to 8 individually cropped out view areas can be streamed simultaneously. P-Iris control provides optimal depth of field, resolution, image contrast and clarity. Remote zoom and focus eliminate the need for hands-on fine tuning. AXIS P3367-V has support for digital pan/tilt/zoom, two-way audio, audio detection and input/output ports for external devices.

- > [HDTV 1080p/5 MP](#)
- > [P-Iris control](#)
- > [Remote zoom and focus](#)
- > [I/O ports and two-way audio](#)
- > [IK10 vandal-resistance](#)



# AXIS P3367-V Network Camera

<b>Camera</b>		Detection, AXIS Digital Autotracking and third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	
<b>Image sensor</b>	Progressive scan RGB CMOS 1/3.2"	<b>Event triggers</b> Analytics, Edge storage events, External input	
<b>Lens</b>	3-9 mm, F1.2 Horizontal angle of view: 84°-30° Vertical angle of view: 63°-22° Varifocal, Remote focus and zoom, P-Iris control, IR corrected	<b>Event actions</b> File upload: FTP, FTPS, HTTP, HTTPS, network share and email Notification: email, HTTP, HTTPS and TCP Video recording to edge storage Pre- and post-alarm video buffering External output activation, Audio recording to edge storage, Play audio clip Preset positions, Guard tour	
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Data streaming</b> Event data	
<b>Minimum illumination</b>	Color: 0.2 lux, F1.2, B/W: 0.04 lux, F1.2	<b>Built-in installation aids</b> Remote zoom, Remote focus, Pixel counter	
<b>Shutter time</b>	1/28000 s to 2 s	<b>General</b>	
<b>Camera angle adjustment</b>	Pan 360°, Tilt 160°, Rotation 340°	<b>Casing</b> Polycarbonate transparent dome, aluminum inner camera module with encapsulated electronics IK10 impact-resistant casing with aluminum base Color: White NCS S 1002-B. For repainting instructions and impact on warranty, contact your Axis partner.	
<b>Video</b>		<b>Memory</b> 512 MB RAM, 128 MB Flash	
<b>Video compression</b>	H.264 Baseline and Main Profile (MPEG-4 Part 10/AVC), Motion JPEG	<b>Power</b> Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 2 Max 6.2 W	
<b>Resolutions</b>	2592x1944 (5 MP) to 160x90	<b>Connectors</b> RJ45 10BASE-T/100BASE-TX PoE Terminal block for 1 alarm input and 1 output, 3.5 mm mic/line in, 3.5 mm line out	
<b>Frame rate</b>	2 MP 4:3 (1600x1200) and HDTV 1080p (1920x1080) capture modes: 30 fps in all resolutions, 3 MP capture mode: 20 fps in all resolutions, 5 MP capture mode: 12 fps in all resolutions	<b>Edge storage</b> Support for SD/SDHC/SDXC card Support for recording to dedicated network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264 and Motion JPEG, Controllable frame rate and bandwidth, VBR/MBR H.264	<b>Operating conditions</b> 0 °C to 50 °C (32 °F to 122 °F) Humidity 10-85% RH (non-condensing)	
<b>Multi-view streaming</b>	Up to 8 individually cropped out view areas When streaming 4 view areas and 1 overview in VGA resolution, the frame rate is 12 fps per stream (5 MP capture mode) or 20 fps per stream (3 MP capture mode)	<b>Storage conditions</b> -40 °C to 65 °C (-40 °F to 149 °F)	
<b>Pan/Tilt/Zoom</b>	Digital PTZ Preset positions, Guard tour	<b>Approvals</b> EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, EN 50581, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78 IEC/EN/UL 60950-1 IEC 62262 IK10	
<b>Image settings</b>	Compression, Color, Brightness, Sharpness, Contrast, White balance, Exposure control, Exposure zones, Backlight compensation, Fine tuning of behavior at low light, Text and image overlay, Mirroring of images, Privacy mask Rotation 0°, 90°, 180°, 270°, including Corridor Format Wide Dynamic Range - Dynamic Contrast	<b>Weight</b> 730 g (1.6 lb)	
<b>Audio</b>		<b>Dimensions</b> Ø148 x 104 mm (Ø5 13/16 x 4 1/16 in)	
<b>Audio streaming</b>	Two-way audio	<b>Included accessories</b> Installation Guide, Windows decoder 1-user license, Resistorx T20 screw driver, Drill hole template Connector kit, Smoked dome	
<b>Audio compression</b>	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Configurable bit rate	<b>Video management software</b> AXIS Camera Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/techsup/software">www.axis.com/techsup/software</a>	
<b>Audio input/output</b>	External microphone input or line input, Line output	<b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese	
<b>Network</b>		<b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>	
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log	a. <i>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<a href="http://www.openssl.org/">http://www.openssl.org/</a>), and cryptographic software written by Eric Young (<a href="mailto:eyay@cryptsoft.com">eyay@cryptsoft.com</a>).</i>	
<b>Supported protocols</b>	IPv4/IPv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMPv1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH	<b>More information is available at <a href="http://www.axis.com">www.axis.com</a></b>	
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform, specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-click Connection ONVIF Profile S, specification at <a href="http://www.onvif.org">www.onvif.org</a>		
<b>Analytics</b>	Video motion detection, Active tampering alarm, Audio detection Support for AXIS Camera Application Platform enabling installation of AXIS Video Motion Detection 3, AXIS Cross Line		